## **SymPOS**

Pro

**SYSTEM** 

**LCD Touch Panel** 

Panel I/O

Audio

Construction

**Power** 

Peripheral (USB Interface)

Certificate

Dimensions (WxDxH)mm

**Environment** 

**OS Supported** 



## **Specifications**

Motherboard PE2

Processor Intel® Elkhart Lake Celeron®J6412 @ 2.0GHz,

up to 2.60 GHz

Chipset Chipset integrated

System Memory 1 x 8GB DDR4 SO-DIMM memory (Max. support up to 16GB)

Storage Device 1x128GB M.2 SSD asstandard

TPM Intel F/W

LCD Touch Panel 15.6" 16:9 TFT LCD

Brightness 350 nits

Resolution 1920 x 1080, Full HD

Touch Screen Super slim bezel true-Flat PCAP multi-touch screen

**USB Port** 4 x USB 2.0, 3 x USB 3.1

COM Port 2 x COM (RJ48 connectors that support DC+0/5/12v by

BIOS setting, default setting is 0v)

LAN Port 1 x Gigabit Ethernet by RJ-45

Cash Drawer 1 x RJ11 (supports 2 cash drawers), DC 24V/12V by

Jumper setting

Type-C 1 x Type-C (DP+PD)

DC-Jack 1 x DC-jack with lock

Power Button 1

Internal Speaker 2 x 2W

Die-cast aluminum housing with plastic covers

LED Indicator 1 for Power LED

Power Adapter 65W adaptor, DC+19V

iButton reader / RFID reader / Fingerprint reader / 2D scanner 2x20 character LCM / 3-Track MSR USB interface / 10.1" Resolution 1280 x 800 (16:10 wide screen),

USB interface

CE/FCC/LVD

359.8 x 178.5 x 261.1mm

Operating Temperature  $0 \sim 40^{\circ}$ C

Windows10 & 11 (64 bit) / Linux